# Sinolift - For material handling

## www.sinolift.com



(( A G

# **Hand Pallet Truck** NP Series

- A quality built truck for a long trouble free life
- Steering arc 210°. Large 180mm dia. steer wheels on articulated axle.
- 10 grease nipples for the most heavily used points.
- A built-in overload valve and totally sealed hydraulic pump.
- Hvdraulic pump seals made in Japanese
- Heavy duty 1 piece "C" section forks for greatest strength and durability.
- Hydraulic pump unit has a 3 year warranty.
- Materials and specification are subject to change without notice.
- o Load rollers: Single or Tandem Nylon, Polyurethane (single nylon is standard).
- Steering wheel: Nylon or Polyurethane (nylon is standard).



Model	Capacity	Fork Width	Fork Length	Min. Height	Msx. Height	Steer Wheel	Load Wheel	Weight
	kg	mm	mm	mm	mm	mm	mm	kg
NP10-48	1000	460	810	80	200	Ø180*62	Ø78*100 (single)	66
NP10-49		460	980					70
NP10-58		520	810					66
NP10-59		520	980					70
NP10-510		520	1070					71
NP10-511		520	1150					73
NP10-712		685	1220					79
NP15-48		460	810		200	Ø180*62	Ø78*100 (single)	66
NP15-49		460	980	80				70
NP15-59		520	810					66
NP15-58		520	980					70
NP15-510	1500	520	1070					71
NP15-511		520	1150					73
NP15-610		600	1070					77
NP15-76		685	650					68
NP15-710		685	1070					76
NP15-712		685	1220					79
NP25-58		520	810			Ø180*62	Ø78*100	67
NP25-59	2500	685	980	80	200		(single)or	71
NP25-510		685	1070				Ø78*70	72
NP25-511		520	1150				(tandem)	75
NP25-712		685	1220					80
NP30-510		520	1170	80	200	Ø180*62	Ø78*100 (single)or Ø78*70	84
NP30-511	3000	520	1150					90
NP30-712		685	1220				(tandem)	100

- 1.2000kg/4400lbs,3500kg/7700lbs,5000kg/11000lbs capacity are also available.
- 2. Hand brake, food brake and parking brake is optional.
- 3.Option: Variety size of Polyurethane, Nylon or Rubber material wheels. Single or tandem load roller.
- 4. Spercial size of width and length can be made according to customer's requirement.
- Model C is the standard handle, but model A, B or D is available
- The control lever with 3 positions for Lifting, Lowering and Neutral movement makes the trucks easy, safe and pleasent to use





( E & 65

# Hand Pallet Truck DF Series


- The oil pump body is made by way of welding the prefabricated parts together first, then machining the welded body.
- Ergonomic Large Rubber handle with three control lever.
- Special lowering valve to control the trucks durable.
- Chrome piston and ram for smooth operation and prevents excessive wear on the pump & seal.
- Excellent turning angle of 180 degree facilities.
- Number of pump strokes-10. Lift height per stroke:11mm.
- Spray plastic painting surface.
- o Option: Nylon wheel, polyurethane wheel, rubber wheel. Single fork roller or tandem fork roller.
- Remark: Special size for width and length can be made according to customer's requirement.

Model		DF20 2000		<b>DF25</b> 2500		<b>DF30</b> 3000	
Capacity Q	kg						
Min.fork height h	mm	85	75	85	75	85	75
Max.fork height h1	mm	200	190	200	190	200	190
Steering wheel	mm	Ф200х50	Φ180x50	Ф200х50	Ф180x50	Ф200х50	Ф180×50
Load roller Single	mm	Ф80х93	Ф74х93	Ф80х93	Ф74х93	Ф80х93	Ф74х93
	mm	Ф80х70	Ф74х70	Ф80x70	Ф74х70	Ф80х70	Ф74х70
Size of fork e*s	mm	160×60					
Width overall forks B	mm	450/520/550/685					
Fork length I	mm	800/900/1000/1100/1150/1220					











### ■ Feature:

- GS/TUV approved in Germany.
- 3 year warranty period.
- Lighter weight easier rolling design.
- Fully rebuildable pump unit with overload valve.
- Hard chrome-plated lift ram and pump piston.
- Entry & exit ramps for prolonged trouble-free use.
- High strength, one-piece tapered forks with precision size.
- 3 coats stoving-paint.
- Heavy duty ball bearings for lower maintenance.
- Highest quality seals and wipers.
- Easy to use 3-position control lever.
- Assemble instruction and parts book with (itemized prices) are supplied.

### Options:

- For roller: single or tandem, Polyurethane or Nylon.
- Low-profile: Min. fork height 35mm.
- Galvanized steel pallet truck.
- Stainless steel pallet truck.
- Pallet truck with brake system.
- Pallet truck with scale.
- Over length and over width pallet trucks are available.
- OEM productions are acceptable.



			11/0 F 22/20 1/11/21 F 22/41/11				
Model	711		NA15/NA20/NA25/NA30				
Capacity		kg	1500/2000/2500/3000				
Max.Fork Height	H2	mm	95/121/165/195/200				
Min.Fork Height	HI	mm	35/51/65/75/80				
Fork Length	1.1	mm	B10/980/1070/1150/1220				
Overall Length	L2		390+L1				
Overall Fork Width	W 1	mm	460	520	685		
Single Fork Width	W 2	mm	150				
Load Roller	В	mm	Ø78×70/Ø78×100 Nylon/Polyurethane				
Steering Wheel	A	mm	Ø200(Ø180) Nylon/Polyurethane/Rubber				
Net.Weight		kg	84	89	92		
Quantities/20ft Container		pcs	180		174		

Remark: 3500kg(NA35)/5000kg(NA50) available on request