



Mini Winch Stacker LS & PM Series

Light weight design, very easy to operate by hand winch, suitable for supermarket, office, warehouse, narrow area, etc.

- Robust, steel construction.
- Manoeuvrable, extremely easy to use.
- Cable winch lifting system with fully cable housing.
- LS can be with platform or adjustable forks.
- Conforms to EN1757-1.



Standard adjustable forks



New optional adjustable forks

Model		LS80	LS150	PM120
Capacity	kg	80	150	120
Lifting Height	mm	1100	1100	1050
Min.fork height	mm	70	70	95
Fork length	mm	500	500	400
Platform size	mm	500x530x90	500x530x90	//
Fork overall width adjustable	mm	132-520	132-520	345-485
Overall dimensions	mm	865x550x1470	830x550x1470	800x460x1370
Net weight	kg	52	52	31



LS80/LS150 ↑


PM120 ↑

Mini Hydraulic Stacker TFB Series

- Easy to operate lifts are available in accurate steel or aluminum construction for long life.
- Lift and transport loads from delivery trucks to docks, maintenance work or use in inventory items.
- Top quality hydraulic pump and cylinder with German seals.
- Top of stroke bypass valve built in.

Model		TFB40-110	TFB40-130	TFB40-150	TFB40-160
Capacity	kg	400	400	400	400
Lowest Height	mm	90	90	90	90
Max. Height	mm	1100	1300	1500	1600
Forks Length *	mm	610	610	610	800
Forks Width *	mm	550	550	550	580
Overall Width	mm	1370	1570	1770	1950
Front Wheel	mm	Ø100	Ø100	Ø100	Ø100
Rear Wheel	mm	Ø152	Ø152	Ø152	Ø152
Net Weight	kg	103	108	113	187

1, * the forks can be changed to platform.
2, Type (I) and type (II) type can be exchangeable.



Hand lever stroke is available



Ø100,Ø150,Ø200,Ø250 wheels are option




Type (I) ↑

Type (II) ↑

Hand Mini Stacker TF Series

Our mini stackers are excellent for everyday light duty work area where loads to be lifted far exceed "the Manual Handling Directive" but do not demand a heavy duty industrial stacker.

- With capacities of 200/400kg respectively and three lift height options.
- Smooth Operating Twin Speed foot pump.
- Positive lifting.
- Pressure / Overload Valve.
- Smart chromium plated frame.
- Powder coated platform.
- Smooth running braked steer wheels.
- Unique design makes lifting and stacking function together.
- CE marked and supplied with certificate of conformity.
- Conforms to EN1757-1.



With safeguard organic glass



Standard platform type

Model		TF20-85	TF20-120	TF40-85	TF40-120	TF40-150
Capacity	kg	200	200	400	400	400
Platform Height Max.	H mm	850	1200	850	1200	1500
Platform Height Min.	h1 mm	200	200	200	200	200
Platform Length	L mm	600	600	650	650	650
Platform Width	W mm	500	500	550	550	550
Load Roller	mm	Ø125	Ø125	Ø150	Ø150	Ø150
Steering Roller	mm	Ø125	Ø125	Ø150	Ø150	Ø150
Net Weight	kg	53	58	72	78	83

1, Except for platform, the optional fixed forks or adjustable forks are available.



A. Standard platform



B. Optional fixed forks



C. Optional adjustable forks

Hand Mini Stacker TFD Series

- Low profile forks can lift the pallet easily.
- Easier and faster lifting operation.
- High quality hydraulic motor made in Italy.
- Service free battery.
- Conforms to EN1757-1.

Model		TFD20-85	TFD20-120	TFD40-85	TFD40-120	TFD40-150
Capacity	kg	200	200	400	400	400
Min. Fork Height	mm	80	80	80	80	80
Max. Fork Height	mm	850	1200	850	1200	1500
Fork Length	mm	600	600	650	650	650
Adjustable Fork Width	mm	215-500	215-500	235-500	235-500	235-500
Single Fork Width	mm	100	100	110	110	110
Dia of Front Wheel	mm	Ø75				
Dia of Steering Wheel	mm	Ø125				
Chassis Height	mm	32.5	32.5	32.5	32.5	32.5
Power Pack Motor	KW	0.7				
Battery	V/Ah	12/60	12/60	12/70	12/70	12/70
Overall Length	mm	1020	1020	1100	1100	1100
Overall Width	mm	560	560	590	590	590
Overall Height	mm	1080	1435	1060	1410	1710
Option Platform	mm	LP10(610 x 530)			LP20(660 x 580)	
Net weight	kg	90	97	105	116	122
Minimum Qty.	pcs	2	2	2	2	2

1, Except for platform, the optional fixed forks or adjustable forks are available.



With safeguard organic glass



Standard platform type