



### Scissor Lift Table ET Series

- Heavy Duty Design.
- lift tables meet EN norm and ANSI/ASME safety standards.
- These models can be used in above-floor or in-floor pit applications.

#### Standard Safety Features

- Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- Low-tension (24V) control box with up-down buttons.
- Internal power pack equipped with relief valve against overloading and compensated flow for controlled lowering speed.
- Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst
- Safety clearance between scissors to prevent trapping during operation.

#### Other Standard Features

- Self lubricating bushings on pivot points.
- Removable lifting eye to facilitate handling and lift table installation.
- High quality AC power packs are made in Europe.



Removable lifting eye



ET1001 ↑



ET4001 ↑

1KG=2.2LB 1INCH=25.4MM

Model		ET1001	ET1002	ET2001	ET2002	ET4001	ET4002
Rated Capacity	kg	1000	1000	2000	2000	4000	4000
Min. Height of Table	mm	205	205	230	230	240	240
Max. Height of Table	mm	1000	1000	1050	1050	1100	1100
Table Dimensions	mm	820x1300	1000x1600	850x1300	1000x1600	1200x1700	1200x2000
Weight	kg	160	186	235	268	375	405
Packing Dimensions	mm	1310x820x210	1610x1010x210	1310x860x240	1610x1010x240	1710x1210x250	2010x1210x250

### Double Scissors Lift Table ETW Series

- Maximize worker and machine productivity by positioning work at just the right level.
- Minimize bending, lifting, reaching and the risk of back injury.
- Internally mounted power unit can be easily removed for repair or maintenance.
- AC or foot pump is available.

#### Other Standard Features

- Self lubricating bushings on pivot points.
- Removable lifting eye to facilitate handling and lift table installation.
- High quality AC power packs are made in Europe.

Model		ETW1000	ETW2000	ETW4000
Capacity	kg	1000	2000	4000
Lowered Height	mm	305	360	400
Raised Height	mm	1780	1780	2050
Platform Size	mm	820x1300	850x1300	1700x1200
Base Frame Size	mm	630x1240	785x1220	1600x900
Lift Time	mm	35~45	35~45	55~65
Power Pack	/	380V/50HZ, AC 1.5kw	380V/50HZ, AC 2.2kw	380V/50HZ, AC 2.2kw
Net Weight	mm	210	295	520




ET4001 ↑



1KG=2.2LB 1INCH=25.4MM

### Low Profile Lift Table ETY Series

- Heavy duty design with larger platform.
- These tables achieve a low closed height, eliminating the need for a pit installation.
- They are manufactured to all European safety standards including EN1570:1999.
- Remote power pack with pedestal and controls, protected to IP54.
- Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- 24V control box with UP and DOWN buttons and emergency stop.
- External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply is AC 380V/50HZ/3 phase.
- Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- Removable lifting eyes to facilitate handling and installation of the lift table.
- Oils bushings on pivot points.
- Loading ramp is standard equipment.



Aluminum Safety Bar

1KG=2.2LB 1INCH=25.4MM

Model		ETY1001	ETY1002	ETY1501	ETY1502	ETY2001	ETY2002
Rated Capacity	kg	1000	1000	1500	1500	2000	2000
Min. Height of Table	C mm	85	85	105	105	105	105
Max. Height of Table	H mm	860	860	870	870	870	870
Table Dimension	LxB mm	1450x1140	1600x1140	1600x800	1600x1000	1600x1000	1600x1200
Weight	kg	357	364	362	401	405	419

### Low Profile Lift Table ETU Series

- "U" and "E" shaped lift tables are specially developed for efficient handling of pallets, No loading ramp is necessary. Before deciding which model and design of lift table is required consider all conditions.
- Remote power system, easy for controlling, convenient for maintenance.
- Electronic controlling box with UP, DOWN & Emergency buttons.
- Specially designed in "U" shape for handling pallets and boxes.
- Electric controlling system is imported from Europe.
- Conforms to EN1570 and BSEN60204-1.



1KG=2.2LB 1INCH=25.4MM

Model		ETU600	ETU1000	ETU150
Capacity	kg	600	1000	1500
Lowered Height	C mm	85	85	105
Raised Height	H mm	860	860	860
Platform Size	LxB mm	1450x985	1420x1140	1600x1160
Net Weight	kg	207	280	364
Packing Dimension	mm	830x520x410	830x520x410	900x560x370

